



Get ahead with the 27" G2741HSU Black Hawk monitor with IPS Panel Technology and 1ms MPRT


Indulge in exceptional gaming excellence with the 27" G2741HSU monitor. This display boasts cutting-edge IPS panel technology, a 144Hz refresh rate, and an ultra-swift 1ms MPRT response time. Elevate your gaming adventure to the next level, thanks to FreeSync Technology and the Black Tuner function, ensuring crystal-clear visibility even in the darkest scenes.

Available also with height adjustable stand : [G-Master_GB2741HSU-B1 \(1920x1080\)](#) and [G-Master_GB2741QSU-B1 \(2560x1440\)](#)



144Hz

Rapid refresh rate and frame rate guarantee smooth, blur free and judder free graphics, with lower latency and lag improving response times for fast paced games. Especially suited to the fast pace games like FPS, racers, MOBA and sports where the 144Hz refresh rate delivers the crisp and sharp images needed to raise your game.



1ms

Fast response time is key to ultra-smooth gaming. It reduces ghosting and blurring providing the user with an improved graphic performance.

01 DISPLAY CHARACTERISTICS

Diagonal	27", 68.6cm
Panel	IPS, matte finish
Native resolution	1920 x 1080 @144Hz
Aspect ratio	16:9
Panel brightness	350 cd/m ²
Static contrast	1500:1
Advanced contrast	80M:1
Response time (MPRT)	1ms
Viewing zone	horizontal/vertical: 178°/178°, right/left: 89°/89°, up/down: 89°/89°
Colour support	16.7mln
Horizontal Sync	30 - 163kHz
Viewable area W x H	597.9 x 336.3mm, 23.5 x 13.2"
Pixel pitch	0.311mm
Colour	matte, black

02 INTERFACES / CONNECTORS / CONTROLS

Signal input	HDMI x1 (v.1.4, max 1920 x 1080 @144Hz) DisplayPort x1 (v.1.2, max 1920 x 1080 @144Hz)
USB HUB	x2 (v.2.0)
HDCP	yes
Headphone connector	yes

03 FEATURES

Blue light reducer	yes
Flicker free	yes
Adaptive Sync support	FreeSync - 1920 x 1080 @48-144Hz
OSD languages	EN, DE, FR, ES, IT, RU, JP, CZ, NL, PL, UA
Control buttons	Joystick / Power Button: Power / Menu (Center), Up / Input Select, Down, Right / Volume / Mute Audio, Left / Brightness / Adaptive Sync / Night Mode / Motion Blur Reduction / i-Style Colour / ECO
User controls	picture adjust (contrast, brightness, OD, Adaptive Sync, Adv. Contrast, Night Mode, Motion Blur Reduction, Gamma), input select (Auto/Manual, HDMI, DP), audio settings (volume, mute audio), store user settings (user modes), colour settings (6-Axis, colour temperature, user preset, i-style colour, blue light reducer, black tuner), image adjust (sharpness, RGB range, video mode adjust, x-res technology), language, setup menu (OSD h. position, OSD v. position, OSD time, OSD background, OSD rotate, opening logo, power LED, ddc/ci control), display information, reset (reset all)
Speakers	2 x 2W
Convenience	Kensington-lock™ prepared, DDC/CI, DDC2B, Mac OSX

04 MECHANICAL

Display position adjustments	tilt
Tilt angle	22° up; 4° down
VESA mounting	100 x 100mm

05 ACCESSORIES INCLUDED

Cables power (1.5m), USB (1.5m), HDMI (1.5m)

Other quick start guide, safety guide

06 POWER MANAGEMENT

Power supply unit internal

Power supply AC 100 - 240V, 50/60Hz

Power usage 16W typical, 0.5W stand by, 0.3W off mode

07 SUSTAINABILITY

Regulations CE, TÜV-Bauart, EAC, PSE, RoHS support, ErP, WEEE, VCCI, REACH, UKCA

Energy efficiency class (Regulation (EU) 2017/1369) C

REACH SVHC above 0.1%: Lead

08 DIMENSIONS / WEIGHT

Product dimensions W x H x D 611.5 x 432 x 349mm

Box dimensions W x H x D 688 x 442 x 126mm

Weight (without box) 4.0kg

Weight (with box) 5.3kg

EAN code 4948570126330

